

## MB 250/50 Combination Safety Shower and Eyebath



### Description

The MB 250/50 Combination Emergency Safety Shower / Body Shower or Drench Shower / Deluge Shower including Eyebath / Face Wash Fountain suitable for outdoor use (frost protected) and floor mounting. The insulated stand pipe is equipped with heat tracing (on request the tracing can be omitted). This model has a 1¼" BSP standpipe and Floor mounting plate and is combined with the MB 50 Eyebath / Face Wash Fountain which has an "unbreakable" ABS bowl and hinged lid (including sign). The lid is at the same time the operation of the Eyebath (pull forwards down and the water starts running). When the lid is pushed back and closed the eyebath stops automatically. Because of this hinged lid the Eyebath remains clean and hygienic.

The Eyebath is equipped with diffusers (optional supplemented with black rubber Eye cups). These diffusers give a gentle aerated soft spray pattern which feels pleasant for the eyes. A drain is present on the bowl of the Eyebath. Also a Flow regulator is present on the unit in order to achieve a good spraying pattern. The Eyebath drains automatically empty after usage. Standard we have a bottom water inlet, but this can be changed to any position you require.

Special Shower head (spray angle 60° and gives rotation to the water) for an effective and efficient operation. Stainless Steel operation Pull rod for Body shower activation. This model is frost protected up to and including -30°C, at your request it is also possible to obtain a model suitable for lower temperatures. Minimum water pressure is 2 bar. The system is also available for rental.



Eye bath (closed)



Eye bath (open)



Eye bath (Spray pattern)



Also available in  
"Aluminum outer jacket"  
version



Foot treadle (Stainless  
Steel)



Foot treadle (small) made  
from Glass Reinforced  
Plastic

## All product options

There is also the possibility to protect the water supply pipe against frost with the extra tracing or the MB 700. Click on the product options below for more information.



Extra tracing



MB 700 frost protected connection

## Specifications

- Water connection: 1¼" BSP Female or different on your request
- water pressure 2 ba
- Body Shower water supply: 60 or 80 liter per minute
- Eyebath water supply: 12 liter per minute
- manual operation
- color: different colors
- material: galvanized steel, Stainless Steel, brass, plastic
- Frost protected up to and including -30°C
- Floor mounting plate 230x230 mm, holes 4xø15 mm H.t.H. 180 mm
- meets the following standards: CE EN 15154 & ANSI Z 358.1

## All product options

- foot pedal
- proximity switch
- automatic flushing unit
- cabin / booth
- flow regulator
- filters
- light
- sign
- hand held shower
- black rubber eye cups
- heater
- Y-strainer filter
- mixing valve
- panel type foot control
- thermostat
- frost free connection piece MB 700
- more options on request



Insulindeweg 15  
1462 MJ Middenbeemster  
The Netherlands

[www.matcon.com](http://www.matcon.com)

[info@matcon.com](mailto:info@matcon.com)

+31 (0)299 684468

KvK: Alkmaar 37093381