

MB 2000 Tank Shower (1500 liter)



Description

The MB 2000 1500 liter Tank Shower / Emergency Safety Shower or Drench Shower / Deluge Shower Standard suitable for outdoor use frost protected or in warm / hot environments cooled / chilled water and areas where no fixed water supply is available or too little water pressure is present. The unit is well insulated and suitable for outdoor installation (frost protected). As an option the tank shower can be equipped with a heater for body shower and Eyebath in order to supply warm water, this can optionally be specified when ordered.

If you choose an Eyebath as an extra option, the Tank Shower is standard combined with the MB 75 Eyebath / Face Wash Fountain with "unbreakable" ABS bowl and hinged lid (including sign). The lid is at the same time the operation of the Eyebath (pull backwards up and the water starts running). When the lid is pushed back and closed the eyebath stops automatically. Because of this hinged lid the Eyebath remains clean and hygienic. On the interior of the lid a mirror is present. This model is a larger version of the MB50.

The tank shower is also available with a cooling unit (chiller) so that the water is cooled in a warm / hot environment. Signs and also a test handle are standard present. The test handle is helpful to be able to test the Body Shower externally easily. The frame is made of stainless steel and the tank is made of fiberglass reinforced polyester material. The Body Shower has a special Shower head (spray angle 60° and gives rotation to the water) for an effective and efficient operation or a low pressure special shower head. The operation will be done by means of Push Bar ("Panic-Bar" push down for operation). The standard spray time of the Body Shower is more than 18 minutes (80 liters per minute), due to different shower heads the duration can be made longer.

It is also possible to connect the tank shower to a permanent water supply (than the Tank Shower remains operational), but this is not necessary. If the water tank is filled the tank shower will operate correctly. The unit is standard suitable for Normal Zone, on request an Explosion or Flame proof / ATEX version is available. Tank Showers are available for rental.



MB 2000 Tank Shower



MB 2000 no side panels




Product option




Product option



Product option



Product option



Product option

Specifications

- Water connection: 3/4" BSP Female
- content 1500 liter
- float valve
- overflow pipe
- test lever
- color: different colors
- material
 - The frame is made of stainless steel
 - The tank is made of fiberglass reinforced polyester material
- meets the following standards: CE EN 15154 & ANSI Z 358.1

All product options

- heater
- chiller
- eyebath (MB 75)
- proximity switch
- light
- hand held shower
- foot pedal
- automatic dump for refreshing water
- PVC strip screens
- visual alarm
- side panels (3 pieces)
- automatic flushing unit
- level indicator
- temperature and level alarm
- temperature indicator (thermometer)
- level indicator
- panel type foot control
- drain sump
- anti-bacterial growth system
- more options on request



Insulindeweg 15
1462 MJ Middenbeemster
The Netherlands

www.matcon.com

info@matcon.com

+31 (0)299 684468

KvK: Alkmaar 37093381