



Description

The MB 310 Emergency Safety Shower / Body Shower or Drench Shower / Deluge Shower suitable for outdoor use (frost protected by means of self draining) on a self-draining stand pipe. Special Shower head (spray angle 60° and gives rotation to the water) for an effective and efficient operation. The operation will be done by means of Push Flag (push down for operation). The self draining valve is located underground (below frost line). This valve should be placed in a drainbed so that the valve and standpipe drains easily empty. As an option we can offer a concrete drain sump where this selfdraining valve is placed in. For this unit there is no electrical connection required for frost protection. The self-draining valve can also be installed above ground level (model MB 310 A). Minimum water pressure is 2 bar.



MB310

Specifications

- Water connection: 1¼" BSP Male
- water pressure 2 bar
- Water supply: 60 or 80 liter per minute
- manual operation
- color: different colors
- material: galvanized steel (possible with coating), Stainless Steel, brass, self draining valve remains from brass
- meets the following standards: CE EN 15154 & ANSI Z 358.1

All product options

- foot pedal
- proximity switch
- automatic flushing unit
- cabin / booth
- flow regulator
- filters
- light
- sign
- heater
- Y-strainer filter
- mixing valve
- panel type foot control
- concrete drain sump and connection piece in drain sump
- more options on request



Insulindeweg 15
1462 MJ Middenbeemster
The Netherlands

www.matcon.com

info@matcon.com

+31 (0)299 684468

KvK: Alkmaar 37093381