



Description

The MB 50 ST. DR. Eyebath / Face Wash Fountain with an “unbreakable” ABS bowl and hinged lid (including sign) suitable for (tropical) outdoor use, resistant to high temperatures (solar radiation) by means of the self draining principle. This model has a 1¼” or 1” BSP standpipe and floor mounting plate. Standard we have a bottom water inlet, but this can be changed to any position you require, in case we install a 3 – way valve (model MB 350 series). The Eyebath has an “unbreakable” ABS bowl and hinged lid (including sign). The lid is at the same time the operation of the Eyebath (pull forwards down and the water starts running). When the lid is pushed back and closed the eyebath stops automatically. Because of this hinged lid the Eyebath remains clean and hygienic. The Eyebath is equipped with diffusers (optional supplemented with black rubber Eye cups). These diffusers give a gentle aerated soft spray pattern which feels pleasant for the eyes. A drain is present on the bowl of the Eyebath. Operation standard by means of foot treadle, but optional possible with panel type foot control. Also a Flow regulator is present on the unit in order to achieve a good spraying pattern. The standpipe and Eyebath are draining completely empty after usage this will prevent unacceptable temperature in the standpipe by solar heating. Minimum water pressure is 2 bar.

Specifications

- Water connection: 1¼" or 1" BSP Female or different on your request
- water pressure 2 bar
- water supply: 12 liter per minute
- foot operation
- flow regulator
- filters
- sign
- dimensions 370x300x300 mm (WxDxH)
- material: galvanized steel (possible with coating), Stainless Steel, brass, plastic
- meets the following standards: CE EN 15154 & ANSI Z 358.1

All product options

- proximity switch
- automatic flushing unit
- light
- sign
- black rubber eye cups
- Y-strainer filter
- mixing valve
- chiller
- panel type foot control
- hand shower
- drain sump
- more options on request



Insulindeweg 15
1462 MJ Middenbeemster
The Netherlands

www.matcon.com

info@matcon.com

+31 (0)299 684468

KvK: Alkmaar 37093381