



Description

The Matcon B.V. film viewers, series LUMAX, are designed and manufactured according to the latest technological requirements and are being used wherever highest demands are placed on film viewing/interpretation.

The equipment corresponds to VDE specification and meets the requirements of DIN EN 25580 and CE certificate.

With this model film densities up to $D = 3,75$ can be evaluated. This model is equipped with a step less brightness regulator and may be operated by hand as well as by foot switch. The illumination circuit is laid-out in such a way that a blinding-free background illumination will always remain, thus reducing the adaption time for the human eye.

The completely coated equipment with a non-staining and shock resistant epoxy-resin assures utmost durability.



LUMAX 40



LUMAX 40

Specifications

- Footswitch
- Front panel for 6 cm film
- Aperture 30 mm dia
- Film format 10 x 24 cm
- Dimensions: 360 mm x 250 mm x 240 mm
- Weight: 8,5 kg
- Voltage: 230 V / 50 Hz
- Viewing Area: 215 x 85 mm
- For film densities: Till D = 3,6
- Brightness: 40.000 cd/m²
- Power: 1000 W

All options

product

- On request



MATCON®

Insulindeweg 15
1462 MJ Middenbeemster
The Netherlands

www.matcon.com

info@matcon.com

+31 (0)299 684468

KvK: Alkmaar 37093381